Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

1. PRODUCT AND COMPANY IDENTIFICATION

Chemical product name : Sikaflex®-263 AP

Supplier's company name, address and phone number

Company name of supplier : Sika Japan Ltd.

Akasaka-K-Tower 7F 1-2-7 Moto-Akasaka Minato-ku Tokyo 107-0051 Japan

Telephone : +81 3 6434 7291

E-mail address : EHS@jp.sika.com

Telefax : -

Emergency telephone number : +81 463 24 4976

Recommended use of the chemical and restrictions on use

Product use : Adhesive

2. HAZARDS IDENTIFICATION

GHS classification of chemical product

Skin corrosion/irritation : Category 3

GHS label elements

Hazard pictograms : None Signal word : Warning

Hazard statements : H316 Causes mild skin irritation.

Precautionary statements : Response:

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Sikaflex®-263 AP



Version Date of last issue: 2020/06/18 **Revision Date:** SDS Number: 2023/04/01 100000011201 Date of first issue: 2017/06/23 4.0

Components

Chemical name	CAS-No.	Concentration (% w/w)	ENCS/ISHL number
Carbon black	1333-86-4	>= 10 - < 20	5-5222
4,4'-methylenediphenyl diisocya- nate	101-68-8	>= 0.1 - < 1	4-118
2-ethyl-2-[[(1-oxoallyl)oxy]methyl]- 1,3-propanediyl diacrylate	15625-89-5	>= 0.1 - < 0.25	2-958, 2-1010

4. FIRST AID MEASURES

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Sikaflex®-263 AP



Version **Revision Date:** SDS Number: Date of last issue: 2020/06/18 2023/04/01 100000011201 Date of first issue: 2017/06/23 4.0

tive equipment and emer-

gency procedures

Personal precautions, protec- : For personal protection see section 8.

Environmental precautions No special environmental precautions required.

Methods and materials for

containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Handling

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Do not get in eyes, on skin, or on clothing.

For personal protection see section 8.

Follow standard hygiene measures when handling chemical

products

Avoidance of contact No data available

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Storage

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type	Control parame-	Basis
·		(Form of	ters / Permissible	
		exposure)	concentration	
4,4'-methylenediphenyl diiso-	101-68-8	OEL-M	0.05 mg/m3	JP OEL
cyanate				JSOH
	Further information: Airway sensitizing agent; Group 1 substances			
	which induce allergic reactions in humans			
		TWA	0.005 ppm	ACGIH

Personal protective equipment

Respiratory protection Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates

Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : paste

Colour : black

Odour : characteristic

Odour Threshold : No data available

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /

Upper flammability limit

: No data available

Lower explosion limit /

Lower flammability limit

No data available

Flash point : ca. 140 °C

(Method: Cleveland open cup)

Decomposition temperature : No data available

pH : Not applicable

Evaporation rate : No data available

Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

Auto-ignition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0.01 hPa

Density and / or relative density

Density : ca. 1.28 g/cm3 (23 °C)

Relative vapour density : No data available

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Carbon black:

Acute oral toxicity : LD50 Oral (Rat): > 8,000 mg/kg

4,4'-methylenediphenyl diisocyanate:

Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:

Acute oral toxicity : LD50 Oral (Rat): 3,680 - 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Carbon black:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h

Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0.87 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Hazardous to the ozone layer

Not applicable

Other adverse effects

Product:

Additional ecological infor-

mation

There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable Proper shipping name : Not applicable

Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen-

ger aircraft)

Not applicable

IMDG-Code

UN number Not applicable Proper shipping name Not applicable Not applicable Class Subsidiary risk Not applicable : Not applicable Packing group Not applicable Labels Not applicable EmS Code Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Refer to section 15 for specific national regulation.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Not applicable to dangerous materials / designated flammables.

Industrial Safety and Health Law

Harmful Substances Prohibited from Manufacture

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

Substances Subject to be Notified Names

Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

Article 57-2 (Enforcement Order Table 9)

Chemical name	Concentration (%)	Remarks
Carbon black	>=10 - <20	-
Methylenebis(4,1-phenylene)	>=0.1 - <1	-
diisocyanate		
1,1,1-trimethylolpropane triacrylate	>=0.1 - <1	From April 1st, 2024

Substances Subject to be Indicated Names

Article 57 (Enforcement Order Article 18)

Chemical name	Remarks
Carbon black	-

Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

Ordinance on Prevention of Lead Poisoning

Not applicable

Ordinance on Prevention of Tetraalkyl Lead Poisoning

Not applicable

Ordinance on Prevention of Organic Solvent Poisoning

Not applicable

Poisonous and Deleterious Substances Control Law

Not applicable

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

Until March 31st, 2023

Not applicable

From April 1st, 2023

Not applicable

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

High Pressure Gas Safety Act

Not applicable

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

JP OEL JSOH : Japan Society for Occupational Health. Recom-

mendation of Occupational Exposure Limits

Sikaflex®-263 AP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2020/06/18

 4.0
 2023/04/01
 100000011201
 Date of first issue: 2017/06/23

ACGIH / TWA : 8-hour, time-weighted average
JP OEL JSOH / OEL-M : Occupational Exposure Limit-Mean

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Se
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. JP / EN