SikaTack Ultrafast



Version	Revision Date:	SDS Number:	Date of last issue: 2020/09/02
3.0	2023/04/02	000000609535	Date of first issue: 2016/12/14

1. PRODUCT AND COMPANY IDENTIFICATION

Chemical product name	SikaTack Ultrafast
-----------------------	--------------------

Supplier's company name, address and phone number

Company name of supplier	:	Sika Japan Ltd. Akasaka-K-Tower 7F 1-2-7 Moto-Akasaka Minato-ku Tokyo 107-0051 Japan
Telephone	:	+81 3 6434 7291
E-mail address	:	EHS@jp.sika.com
Telefax	:	-
Emergency telephone number	:	+81 463 24 4976

Recommended use of the chemical and restrictions on use

Product use	:	Adhesive
-------------	---	----------

2. HAZARDS IDENTIFICATION

GHS classification of chemical product

Acute toxicity (Inhalation)		Category 4
Skin sensitisation	:	Category 1
Reproductive toxicity	:	Category 1B
Specific target organ toxicity - single exposure	:	Category 2 (Central nervous system, Kidney, Liver, respiratory system)
Specific target organ toxicity - repeated exposure	:	Category 1 (respiratory system)
Specific target organ toxicity - repeated exposure	:	Category 2 (Nervous system)
Short-term (acute) aquatic hazard	:	Category 3

GHS label elements

SikaTack Ultrafast



Version 3.0	Revision Date: 2023/04/02	SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
Hazar	rd pictograms		
Signa	l word	: Danger	
Hazar	d statements	Kidney, Liver, respiratory H372 Causes damage to prolonged or repeated ex	y or the unborn child. to organs (Central nervous system, system). organs (respiratory system) through posure. to organs (Nervous system) through posure.
Preca	utionary statements	and understood. P260 Do not breathe mis P264 Wash skin thorough P270 Do not eat, drink or P271 Use only outdoors of P272 Contaminated work the workplace. P273 Avoid release to the	all safety precautions have been read t or vapours. hly after handling. r smoke when using this product. or in a well-ventilated area. c clothing should not be allowed out of
		 P304 + P340 + P312 IF I and keep comfortable for doctor if you feel unwell. P308 + P311 IF exposed CENTER/ doctor. P333 + P313 If skin irritat vice/ attention. P362 + P364 Take off co reuse. Storage: P405 Store locked up. Disposal: 	A: Wash with plenty of water. NHALED: Remove person to fresh air breathing. Call a POISON CENTER/ or concerned: Call a POISON tion or rash occurs: Get medical ad- ntaminated clothing and wash it before
		Disposal:	s/ container to an approved

SikaTack Ultrafast



Version Revision Da 3.0 2023/04/02	e: SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
------------------------------------	--------------------------------	---

Other hazards which do not result in classification None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	ENCS/ISHL number
Carbon black	1333-86-4	>= 10 - < 20	5-5222
xylene	1330-20-7	2	3-3, 3-60
4,4'-methylenediphenyl diisocya- nate	101-68-8	>= 0.1 - < 1	4-118
ethylbenzene	100-41-4	>= 0.3 - < 1	3-28, 3-60
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	>= 0.1 - < 1	3-2492

4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.	
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.	
Most important symptoms and effects, both acute and delayed	:	sensitising effects Allergic reactions See Section 11 for more detailed information on health effects and symptoms. May cause an allergic skin reaction. Harmful if inhaled. May damage fertility or the unborn child. May cause damage to organs.	
3 / 13			

SikaTack Ultrafast



Versic 3.0	n Revision Date: 2023/04/02		SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
			Causes damage to organs throug exposure.	n prolonged or repeated
I	Notes to physician	:	Treat symptomatically.	
5. FIF	REFIGHTING MEASURES			
5	Suitable extinguishing media	:	Carbon dioxide (CO2)	
	Jnsuitable extinguishing nedia	:	Water	
	Hazardous combustion prod- ucts	:	No hazardous combustion produc	ts are known
	Specific extinguishing meth- ods	:	Standard procedure for chemical f	ires.
	Special protective equipment or firefighters	:	In the event of fire, wear self-conta	ained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Handling

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area.

SikaTack Ultrafast



Version 3.0	Revision Date: 2023/04/02		SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
			Follow standard hygiene measu products	res when handling chemical
Avoic	lance of contact	:	No data available	
Hygiene measures		:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	
Stora	age			
Cond	itions for safe storage	:	Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local re	egulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
xylene	1330-20-7	OEL-M	50 ppm 217 mg/m3	JP OEL JSOH
		ation: Group 2: S oxicity in humans	Substances presumed	d to cause
		ACL	50 ppm	JP OEL ISHL
		TWA	20 ppm	ACGIH
4,4'-methylenediphenyl diiso- cyanate	101-68-8	OEL-M	0.05 mg/m3	JP OEL JSOH
			nsitizing agent; Group	1 substances
	which induce a	allergic reactions	in humans	
		TWA	0.005 ppm	ACGIH
ethylbenzene	100-41-4	ACL	20 ppm	JP OEL ISHL
		OEL-M	20 ppm	JP OEL
			87 mg/m3	JSOH
	Further information: Group 2: Substances presumed to cause reproductive toxicity in humans, Skin absorption, Group 2B: pos- sibly carcinogenic to humans			
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Target sub- stance	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	total (o-, m-, p-)methylhipp uric acid		End of shift at end of workweek	800 mg/l	JSOH



SikaTack Ultrafast

ersion 0	Revision Date: 2023/04/02		SDS Numbe 0000006095		Date of last issue: 2020/09/02 Date of first issue: 2016/12/14			
			Methylhip- puric acids	Urine	End of shift (As soon as possible after ex- posure ceases)	1.5 g/g creat- inine	ACGIH BEI	
ethylb	enzene	100-41-4	Mandelic acid	Urine	End of shift	150 mg/g Creatinine	JSOH	
			Mandelic acid + Phenylglyox ylic acid	Urine	End of shift at end of workweek	200 mg/g Creatinine	JSOH	
			Ethylben- zene	Urine	End of shift	15 µg/l	JSOH	
			Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after ex- posure ceases)	0.15 g/g cre- atinine	ACGIH BEI	
Biologi	cal Exposure Limi	ts (Europe)	for EMEA and	d CIS count	ries			
Respir	atory protection	ver tha The imu	ntilation is prov at exposures ar e filter class fo um expected c	ided or expo e within reco r the respirat ontaminant o	sure assess ommended e or must be s concentration	te local exhaust sment demonstr exposure guidel suitable for the n	rates ines. max-	

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, selfcontained breathing apparatus must be used.

- Hand protection
 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
 Eye protection
 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	paste
Colour	:	black
Odour	:	characteristic

SikaTack Ultrafast



Versio 3.0	n Revision Date: 2023/04/02		SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
C	Ddour Threshold	:	No data available	
	Aelting point/range / Freezing point	:	No data available	
E	Boiling point/boiling range	:	No data available	
F	Flammability (solid, gas)	:	No data available	
L	ower explosion limit and uppe. Upper explosion limit / Upper flammability limit	rex :	cplosion limit / flammability limit No data available	
	Lower explosion limit / Lower flammability limit	:	No data available	
F	Flash point	:	ca. 80 °C (Method: closed cup)	
C	Decomposition temperature	:	No data available	
p	Н	:	Not applicable	
E	Evaporation rate	:	No data available	
A	Auto-ignition temperature	:	No data available	
V	/iscosity Viscosity, dynamic	:	No data available	
	Viscosity, kinematic	:	> 20.5 mm2/s (40 °C)	
S	Solubility(ies) Water solubility	:	insoluble	
	Solubility in other solvents	:	No data available	
	Partition coefficient: n- octanol/water	:	No data available	
V	/apour pressure	:	0.01 hPa	
C	Density and / or relative density Density	' :	ca. 1.14 g/cm3 (23 °C)	
	Relative vapour density	:	No data available	
E	Explosive properties	:	No data available	
C	Dxidizing properties	:	No data available	

SikaTack Ultrafast



Versio 3.0	on Revision Date: 2023/04/02		SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
10. 5	TABILITY AND REACTIVITY			
	Reactivity	:	No dangerous reaction knc	own under conditions of normal use.
	Chemical stability		The product is chemically s	stable.
	Possibility of hazardous reac- tions		No hazards to be specially	mentioned.
	Conditions to avoid		No data available	
Incompatible materials		:	No data available	

11. TOXICOLOGICAL INFORMATION

Acute toxicity Harmful if inhaled.		
<u>Components:</u>		
Carbon black: Acute oral toxicity	:	LD50 Oral (Rat): > 8,000 mg/kg
xylene:		
Acute oral toxicity	:	LD50 Oral (Rat): 3,523 mg/kg
4,4'-methylenediphenyl di	-	
Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
ethylbenzene:		
Acute oral toxicity	:	LD50 Oral (Rat): 3,500 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 5,510 mg/kg
3-isocvanatomethyl-3.5.5-	trime	thylcyclohexyl isocyanate:
Acute oral toxicity		LD50 Oral (Rat): 4,814 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0.031 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rat): > 7,000 mg/kg

SikaTack Ultrafast



Version	Revision Date:	SDS Number:	Date of last issue: 2020/09/02
3.0	2023/04/02	00000609535	Date of first issue: 2016/12/14

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility or the unborn child.

STOT - single exposure

May cause damage to organs (Central nervous system, Kidney, Liver, respiratory system).

STOT - repeated exposure

Causes damage to organs (respiratory system) through prolonged or repeated exposure. May cause damage to organs (Nervous system) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

<u>Components:</u> Carbon black: Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l Exposure time: 96 h
xylene: Toxicity to fish (Chronic tox- icity)	:	NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l Exposure time: 56 d
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity) ethylbenzene:	:	NOEC (Daphnia (water flea)): 1.17 mg/l Exposure time: 7 d
Toxicity to fish	:	LC50 (Fish): <= 1 mg/l Exposure time: 96 h

SikaTack Ultrafast



Versio 3.0	n Revision Date: 2023/04/02		SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
	M-Factor (Acute aquatic tox- city)	: 1		
	Persistence and degradabilit No data available	ÿ		
	Bioaccumulative potential No data available			
	Mobility in soil No data available			
	Hazardous to the ozone laye Not applicable	r		
C	Other adverse effects			
Ā	Product: Additional ecological infor- nation	: Th	ere is no data available for this	product.
13. D	ISPOSAL CONSIDERATION	S		
	Disposal methods			
١	Naste from residues	: Se	nd to a licensed waste manage	ment company.
			o not contaminate ponds, waterv l or used container.	vays or ditches with chemi-
(Contaminated packaging		npty remaining contents. spose of as unused product.	
		Do	o not re-use empty containers.	

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG	
UN number	: Not applicable
Proper shipping name	: Not applicable
Class	: Not applicable
Subsidiary risk	: Not applicable
Packing group	: Not applicable
Labels	: Not applicable
IATA-DGR	
UN/ID No.	: Not applicable
Proper shipping name	: Not applicable
Class	: Not applicable
Subsidiary risk	: Not applicable
Packing group	: Not applicable

SikaTack Ultrafast



Version 3.0	Revision Date: 2023/04/02	SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
aircra Packi	ng instruction (cargo	Not applicableNot applicableNot applicable	
UN nu Prope Class Subsi Packi Labels EmS	diary risk ng group s	 Not applicable 	
	port in bulk according	to Annex II of MARPOL 73/78	and the IBC Code
	nal Regulations	supplied.	
	to section 15 for specifi	c national regulation.	
-	i al precautions for use pplicable	r	
15. REGU	LATORY INFORMATIC	N	
Relate	ed Regulations		
Desig	Service Law nated Flammable Subs strial Safety and Health		
	-	ited from Manufacture	
	pplicable		
	Harmful Substances Required Permission for Manufacture Not applicable		
Suba	tances Provented From	n Impairment of Health	

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

Substances Subject to be Notified Names

Article 57-2 (Enforcement Order Table 9)

Chemical name	Concentration (%)	Remarks
Carbon black	>=10 - <20	-

SikaTack Ultrafast



Version 3.0	Revision Date: 2023/04/02	SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14
Xyler	ne	>=1 - <10	-
	ylenebis(4,1-phenylene) cyanate	>=0.1 - <1	-
Ethyl	benzene	>=0.1 - <1	-
	cyanatomethyl-3,5,5- thylcyclohexyl isocyanate	>=0.1 - <1	-

Substances Subject to be Indicated Names

Article 57 (Enforcement Order Article 18)		
Chemical name	Remarks	
xylene	-	
ethylbenzene	-	
Carbon black	-	

Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

Ordinance on Prevention of Lead Poisoning

Not applicable

Ordinance on Prevention of Tetraalkyl Lead Poisoning

Not applicable

Ordinance on Prevention of Organic Solvent Poisoning

Not applicable

Poisonous and Deleterious Substances Control Law

Not applicable

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

Until March 31st, 2023

Class I Designated Chemical Substances

Chemical name	Cabinet Order Number	Concentration (%)
xylene	80	2.0

From April 1st, 2023

Class I Designated Chemical Substances

Chemical name	Administration number	Concentration (%)
xylene	80	2.0

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

High Pressure Gas Safety Act

Not applicable

16. OTHER INFORMATION

Date format

: yyyy/mm/dd

SikaTack Ultrafast



Version 3.0	Revision Date: 2023/04/02	SDS Number: 000000609535	Date of last issue: 2020/09/02 Date of first issue: 2016/12/14			
Full	Full text of other abbreviations					
ACGIH ACGIH BEI JP OEL ISHL JP OEL JSOH		 USA. ACGIH Threshold Li ACGIH - Biological Expose Japan. Administrative Con Japan. The Japan Society mendation of Occupationa 	ure Indices (BEI) htrol Levels r for Occupational Health. Recom-			
JSO	Н		Occupational exposure limits based on biological monitoring			
JP O	IH / TWA DEL ISHL / ACL DEL JSOH / OEL-M	 (JSOH). 8-hour, time-weighted average Administrative Control level Occupational Exposure Limit-Mean European Agreement concerning the International Carriage of Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of 				
CAS DNE EC50	L 0					
GHS IATA IMD0 LD50	G					
LC50)	 test animals) Median lethal concentration (concentrations of the chemical air that kills 50% of the test animals during the observation period) 				
MAR	RPOL	: International Convention for	or the Prevention of Pollution from			
OEL PBT PNE REA	С	and of the Council of 18 D istration, Evaluation, Author	mit ve and toxic			
SVH vPvE		: Substances of Very High (: Very persistent and very b	Concern			

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. JP / EN